



**PART NUMBERS:**

D	1	W	B	*	F
	2	X	S	IE	
	3		A		
	4				



EXAMPLE PART NUMBERING:  
DIWBF/NP/20/050NPT

<b>D</b>	Gland featuring armour specific clamping
<b>1</b>	Neoprene Seal (1) - Silicone Seal (3) - Neoprene/Lead (2) - Silicone/Lead (4)
<b>W</b>	SWA (W) / SWB or STA (X)
<b>B</b>	Aluminium (A) / Brass (B) / Stainless Steel (S)
<b>IE</b>	Integral Earth (see page 43)
<b>F</b>	Multiple Certification
<b>C</b>	PVC Shroud (C) - PCP Shroud (P) - LSOH Silicone Shroud (3)
<b>K-V-H</b>	Locknut, Earth Tag & Nylon (K), Fibre (V) or PTFE (H) IP Washer
<b>S</b>	Including Serrated Washer
<b>1</b>	Quantity per kit
<b>NP</b>	Nickel Plated
<b>20</b>	Gland shell size
<b>050NPT</b>	½"NPT Male Entry Thread

OPTIONAL ACCESSORIES:

<b>LOCKNUT</b>	Brass (ACBLN) / Stainless Steel (ACSLN) / Aluminium (ACALN)
<b>EARTH TAG</b>	Brass (ACBET) / Stainless Steel (ACSET) / Aluminium (ACAET)
<b>IP WASHERS</b>	Nylon (ACNSW) / Fibre (ACFSW) / PTFE (ACPSW)
<b>SERRATED WASHERS</b>	Stainless Steel (ACSSW)
<b>SHROUDS</b>	PVC (ACSPVC) / PCP (ACSPCP) / LSOH Silicone (ACSSIO)

<b>IP RATING:</b>	IP66 & IP68 (50 metres - 7 days), Type 4X
<b>OPERATING TEMP:</b>	Neoprene Seals -35°C to +90°C Silicone Seals -60°C to +180°C
<b>MATERIALS:</b>	Aluminium, Brass or Stainless Steel
<b>PLATING:</b>	Electroless Nickel

**PRODUCT DESCRIPTION**

"D" type single compression glands are certified Flameproof Ex db, Increased Safety Ex eb, Restricted Breathing Ex nR and Dust Protected Ex ta. They are suitable for use in Zone 1 and 2 for Gas Groups IIA, IIB and IIC and additionally for use in Zones 20, 21 and 22 for Dust Groups IIIA, IIIB and IIIC. Additionally certified for Class I Zone 1 & Class I Div 2 installations for use with Marine Shipboard & Tray Cables under NEC & CEC. They provide a controlled Ex db & IP seal on the cable inner sheath and a detachable armour specific clamping system for wire (W), braid/tape (X) armoured cables. The gland has been tested to IP66 and IP68 to 50 metres. The "IE" version allows the gland to be used with HV cables where the fault load is greater than 10.4kA and options are available for use with lead sheath, LSOH cables and extreme temperature applications. A termination suitable for EMC protection can be made using armoured cables with these glands.

**COMPLIANCE STANDARDS:**

EN 60079-0, EN 60079-1, EN 60079-7, EN 60079-15, EN 60079-31  
IEC 60079-0, IEC 60079-1, IEC 60079-7, IEC 60079-31 & IEC 60529  
C22.2 (see certificate) CAN/CSA 60079-0/1/7  
UL514B, UL1203, UL2225, UL50E, ANSI/UL 60079-0/7, ISA 60079-31

CERTIFICATION:

<b>ATEX</b>	II 1D 2G Ex db IIC Gb / Ex eb IIC Gb / Ex ta IIC Da II 3G Ex nR IIC Gc
<b>IECEX</b>	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIC Da
<b>CEC - Canada</b>	Class I Division 2, Groups A, B, C & D Class II Division 1, Groups E, F & G Class III, Type 4X Class I Zone 1 Ex d IIC / Ex e II Class II Division 1, Groups E, F & G Class III, Type 4X Class I Zone 1 AEx e IIC Gb Class II Zone 20 AEx ta IIC Da
<b>NEC - USA</b>	1Ex d IIC Gb X / 1Ex e IIC Gb X / 2Ex nR IIC Gc X / Ex ta IIC Da X
<b>EAC</b>	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIC Da
<b>INMETRO - Brazil</b>	Ex d IIC Gb / Ex e IIC Gb / Ex nR IIC Gc / Ex td A20
<b>CCC - China</b>	II 2G Ex db IIC Gb / II 2G Ex eb IIC Gb / II 3G Ex nR IIC Gc / II 1D Ex ta IIC Da
<b>UKRAINE</b>	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIC Da
<b>ABIS</b>	Specified ABS Rules
<b>LLOYD'S</b>	Ex db IIC Gb / Ex eb IIC Gb / Ex nR IIC Gc / Ex ta IIC Da
<b>RS - Russia</b>	Ex d IC / Ex d IIC / Ex e IC / Ex e IIC / Ex ta IIC / Ex tb IIC

CERTIFICATION No:

<b>ATEX</b>	CML 19ATE1106X & CML 19ATEX4109X
<b>IECEX</b>	IECEX CML 19.0031X
<b>CEC - Canada</b>	CSA 1356011
<b>NEC - USA</b>	CSA 2627370
<b>EAC</b>	RU C-GB.BH02.B.00693-18
<b>INMETRO - Brazil</b>	NCC 13.2186 X
<b>CCC - China</b>	2021321313000406
<b>UKRAINE</b>	CLJ 18.0323 X
<b>CCoE - India</b>	PESO P494321/4 & P494321/13
<b>ABIS</b>	20-LD1944057-PDA
<b>LLOYD'S</b>	LR2124442TA
<b>RS - Russia</b>	19.00189.278

CABLE GLAND SELECTION TABLE  
(ALL DIMENSIONS IN mm)

Gland size	Entry Thread Size		Metric Thread Length [B]	Cable Acceptance Details			Armour Acceptance Range		Nominal Protrusion Length [L]	Dimensions/Weight (Metric)			Shroud Size* (Metric)
	Metric	NPT		Inner Sheath [C]		Outer Sheath [D]	W	X		Across Flats [A]	Across Corners	Weight (Kgs)	
				Min	Max								
16	M16 x 1.5	½" or ¾"	16	3.5	8.4	13.5	0.90	0.15-0.35	57	24.0	26.5	0.128	L24**
16	M20 x 1.5	½" or ¾"	16	3.5	8.4	13.5	0.90	0.15-0.35	59	24.0	26.5	0.139	L24**
20S	M20 x 1.5	½" or ¾"	16	8.0	11.7	16.0	0.90-1.25	0.15-0.35	56	24.0	26.5	0.116	L24**
20	M20 x 1.5	½" or ¾"	16	6.7*	14.0	21.0	0.90-1.25	0.15-0.50	56	30.0	33.0	0.158	L30
25	M25 x 1.5	¾" or 1"	16	13.0	20.0	27.5	1.25-1.60	0.15-0.50	56	38.0	41.4	0.237	L38
32	M32 x 1.5	1" or 1 ¼"	16	19.0	26.3	34.0	1.60-2.00	0.15-0.55	63	46.0	50.6	0.344	L46
40	M40 x 1.5	1 ¼" or 1 ½"	16	25.0	32.2	40.0	1.60-2.00	0.20-0.60	69	55.0	60.5	0.567	L55
50S	M50 x 1.5	1 ½" or 2"	16	31.5	38.2	53.0	2.00-2.50	0.20-0.60	71	65.0	71.5	0.776	L65
50	M50 x 1.5	2"	16	36.5	44.1	53.0	2.00-2.50	0.30-0.80	71	65.0	71.5	0.634	L65
63S	M63 x 1.5	2" or 2 ½"	19	42.5	50.1	65.5	2.50	0.30-0.80	71	80.0	88.0	1.186	L80
63	M63 x 1.5	2 ½"	19	49.5	56.0	65.5	2.50	0.30-0.80	71	80.0	88.0	1.003	L80
75S	M75 x 1.5	2 ½" or 3"	19	54.5	62.0	78.5	2.50	0.30-1.00	79	90.0	99.0	1.408	L90
75	M75 x 1.5	3"	19	60.5	68.0	78.5	2.50	0.30-1.00	79	90.0	99.0	1.163	L90
80	M80 x 2.0	3" or 3 ½"	25	62.2	72.0	84.0	3.15	0.45-1.00	102	104.0	115.2	2.392	L104
80H	M80 x 2.0	3" or 3 ½"	25	62.2	72.0	90.0	3.15	0.45-1.00	102	104.0	115.2	2.481	L104
85	M85 x 2.0	3" or 3 ½"	25	69.0	78.0	90.0	3.15	0.45-1.00	102	104.0	115.2	2.163	L104
90	M90 x 2.0	3 ½" or 4"	25	74.0	84.0	96.0	3.15	0.45-1.00	103	114.0	125.7	2.509	L114
90H	M90 x 2.0	3 ½" or 4"	25	74.0	84.0	102.0	3.15	0.45-1.00	103	114.0	125.7	2.501	L114
100	M100 x 2.0	3 ½" or 4"	25	82.0	90.0	102.0	3.15	0.45-1.00	104	114.0	125.7	2.199	L114

NOTES

- Gland size does not necessarily equate to the entry thread size.
- Dimensions (A) & (B) may differ for glands with non metric entry threads. Please refer to our "Thread Reference Tables" for specific dimensions.
- Assembly instructions must be read prior to installation and adhered to in full.
- Peppers supply products with parallel entry threads that conform to the flameproof threaded joint requirements of IEC/EN 60079-1 and other equivalent standards. We usually incorporate a thread run out according to general machining techniques and parts will not have a full form thread for the entire length. Peppers Cable Glands Limited will not be held responsible for clients' installations where this has not been taken into account.
- When selecting IP Washer & Shroud material for use with glands, please be aware of the accessories temperature range to ensure they are suitable for the intended installation.
- Where approval in addition to ATEX, IECEX and CSA is required, this must be clearly requested at time of enquiry / order.
- \* For gland size 20 the silicone inner seal has a minimum diameter of 9.3 mm and NOT 6.7mm.
- \*\* For gland sizes 16 and 20S when used with ¾" NPT entry thread an L30 shroud would be required.